

PL TANNIN 2

Page: 1

Compilation date: 06/08/2013

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: PL TANNIN 2

Product code: XR0827

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name: droptestkits.com Ltd

4/4A Titley Bawk Avenue

Earls Barton

Northampton

NN6 0LA

United Kingdom

Tel: +44 (0) 1604 686995

Fax: +44 (0) 1604 686997

Email: info@droptestkits.com

1.4. Emergency telephone number

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Skin Corr. 1B: H314

Most important adverse effects: Causes burns.

2.2. Label elements

Label elements under CLP:

Hazard statements: H314: Causes severe skin burns and eye damage.

Signal words: Danger

Hazard pictograms: GHS05: Corrosion



Precautionary statements: P264: Wash hands thoroughly after handling.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P321: Specific treatment (see instructions on this label).

PL TANNIN 2

 P405: Store locked up.

 P501: Dispose of contents/container to hazardous or special waste collection point.

 Label elements under CHIP:

 Hazard symbols:
 Corrosive.

 Risk phrases:
 Risk phrases:

 Safety phrases:
 S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

 Safety phrases:
 S36/37/39: Wear suitable protective clothing, gloves and eye / face protection.

 S45: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

 23. Other hazards

PBT: This product is not identified as a PBT substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

LITHIUM SULPHATE

EINECS	CAS	CHIP Classification	CLP Classification	Percent
233-820-4	10377-48-7	Xn: R22	Acute Tox. 4: H302	10-30%
HYDROCHLC	ORIC ACID			
231-595-7	7647-01-0	C: R34; Xi: R37	Skin Corr. 1B: H314; STOT SE 3: H335	1-10%
ORTHOPHOS	SPHORIC ACID			
231-633-2	7664-38-2	C: R34	Skin Corr. 1B: H314	1-10%
SODIUM TUN	IGSTATE DIHYD	RATE		
236-743-4	10213-10-2	Xn: R22	Acute Tox. 4: H302	1-10%

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin.
 Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Transfer to hospital if there are burns or symptoms of poisoning.
 Eye contact: Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist

- **Eye contact:** Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.
 - Ingestion: Wash out mouth with water. Do not induce vomiting. Give 1 cup of water to drink every 10

Page: 2

PL TANNIN 2

minutes. If unconscious, check for breathing and apply artificial respiration if necessary. If unconscious and breathing is OK, place in the recovery position. Transfer to hospital as soon as possible.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. If unconscious and breathing is OK, place in the recovery position. If conscious, ensure the casualty sits or lies down. If breathing becomes bubbly, have the casualty sit and provide oxygen if available. Transfer to hospital as soon as possible.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: Blistering may occur. Progressive ulceration will occur if treatment is not immediate.

Eye contact: Corneal burns may occur. May cause permanent damage.

- **Ingestion:** Corrosive burns may appear around the lips. Blood may be vomited. There may be bleeding from the mouth or nose.
- **Inhalation:** There may be shortness of breath with a burning sensation in the throat. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Corrosive. In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Notify the police and fire brigade immediately. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

PL TANNIN 2

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Clean-up should be dealt with only by qualified personnel familiar with the specific substance. Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Do not handle in a confined space. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

ORTHOPHOSPHORIC ACID...100%

Workplace exposure limits:					
	State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
	UK	1 mg/m3	2 mg/m3	-	-

8.1. DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Respiratory protection: Self-contained breathing apparatus must be available in case of emergency. Hand protection: Impermeable gloves. Eye protection: Tightly fitting safety goggles. Ensure eye bath is to hand. Skin protection: Impermeable protective clothing.

Section 9: Physical and chemical properties

Page: 4

.

PL TANNIN 2

Page: 5

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Yellow

Odour: Characteristic odour

Solubility in water: Miscible in all proportions

Viscosity: Viscous

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

LITHIUM SULPHATE

ORAL	RAT	LD50	1190	mg/kg	
------	-----	------	------	-------	--

ORTHOPHOSPHORIC ACID...100%

ORL RAT LD50	1530 mg/kg
--------------	------------

PL TANNIN 2

SODIUM TUNGSTATE DIHYDRATE

DERMAL	RAT	LDLO	2000	mg/kg
INHALATION	RAT	4H LC50	5,010	mg/m3
INTRAPERITONEAL	MUS	LD50	145	mg/kg
INTRAPERITONEAL	RAT	LD50	204	mg/kg
ORAL	RAT	LD50	1,453	mg/kg
SUBCUTANEOUS	RAT	LD50	251	mg/kg

Relevant effects for mixture:

Effect	Route	Basis
Corrosivity	OPT INH DRM	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: Blistering may occur. Progressive ulceration will occur if treatment is not immediate.

Eye contact: Corneal burns may occur. May cause permanent damage.

- **Ingestion:** Corrosive burns may appear around the lips. Blood may be vomited. There may be bleeding from the mouth or nose.
- **Inhalation:** There may be shortness of breath with a burning sensation in the throat. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

PL TANNIN 2

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN3264

14.2. UN proper shipping name

Shipping name: CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S.

14.3. Transport hazard class(es)

Transport class: 8

14.4. Packing group

Packing group: |||

14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: E

Transport category: 3

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Section 16: Other information

Other information

Other information:This safety data sheet is prepared in accordance with Commission Regulation (EU) No
453/2010.
* indicates text in the SDS which has changed since the last revision.Phrases used in s.2 and 3:H302: Harmful if swallowed.
H314: Causes severe skin burns and eye damage.
H335: May cause respiratory irritation.
R22: Harmful if swallowed.
R34: Causes burns.
R37: Irritating to respiratory system.

PL TANNIN 2

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.